

## Spouts

## SILVER SERIES



### Standard Features

- Durable full range spout with double o-ring construction
- Chrome plated finish
- Built for high volume
- Fits Krowne Silver Series faucets
- 1 year warranty

### Product Compliance

- NSF-61 & NSF/ANSI 372
- NSF/ANSI/CAN 61: Q<1
- ASME A112.18.1-2012/CSA B125.1-12
- CEC Listed
- Massachusetts Listed



| Model   | Spout Style    | Spout Length | Flow Rate | Height  | Weight    |
|---------|----------------|--------------|-----------|---------|-----------|
| 19-220L | Swing          | 6"           | 1.8 GPM   | 3-3/4"  | 0.5 lbs.  |
| 19-221L | Swing          | 8"           | 1.8 GPM   | 4"      | 0.5 lbs.  |
| 19-222L | Swing          | 10"          | 1.8 GPM   | 4-1/2"  | 0.75 lbs. |
| 19-223L | Swing          | 12"          | 1.8 GPM   | 4-3/4"  | 0.75 lbs. |
| 19-224L | Swing          | 14"          | 1.8 GPM   | 5"      | 0.75 lbs. |
| 19-225L | Swing          | 16"          | 1.8 GPM   | 5-1/2"  | 0.75 lbs. |
| 19-226L | Jointed        | 18"          | 1.8 GPM   | 6-3/4"  | 1.25 lbs. |
| 19-227L | Wide Gooseneck | 3-1/2"       | 0.5 GPM   | 7-1/4"  | 0.5 lbs.  |
| 19-228L | Wide Gooseneck | 6"           | 1.8 GPM   | 8-1/2"  | 0.75 lbs. |
| 19-229L | Wide Gooseneck | 8-1/2"       | 1.8 GPM   | 11-1/2" | 0.5 lbs.  |

#### Warning:

Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes

#### California Prop 65 Warning:

This product can expose you to chemicals including lead and lead compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.cdph.ca](http://www.cdph.ca)