

# Spouts

# ROYAL SERIES



21-420L



21-430L



21-428L

## Standard Features

- Durable full range spout with double o-ring construction
- Chrome plated finish
- Built for high volume
- Fits all Krowne faucets and interchangeable with most brands
- 3 year warranty

## Product Compliance

- NSF-61 & NSF/ANSI 372
- NSF/ANSI/CAN 61: Q<1
- ASME A112.18.1-2012/CSA B125.1-12
- CEC Listed
- Massachusetts Listed



Model	Spout Style	Spout Length	Flow Rate	Height	Weight
21-420L	Swing	6"	1.8 GPM	1"	0.5 lbs.
21-421L	Swing	8"	1.8 GPM	1"	0.5 lbs.
21-422L	Swing	10"	1.8 GPM	2-1/4"	0.75 lbs.
21-423L	Swing	12"	1.8 GPM	2-5/8"	0.75 lbs.
21-424L	Swing	14"	1.8 GPM	3-1/2"	0.75 lbs.
21-425L	Swing	16"	1.8 GPM	4"	0.75 lbs.
21-426L	Jointed	18"	1.8 GPM	4-1/8"	1.25 lbs.
21-427L	Wide Gooseneck	3-1/2"	0.5 GPM	7-1/4"	0.5 lbs.
21-428L	Wide Gooseneck	6"	1.8 GPM	8-1/2"	0.75 lbs.
21-429L	Wide Gooseneck	8-1/2"	1.8 GPM	10"	0.5 lbs.
21-430L	Wide Double Bend	4-1/2"	0.5 GPM	6"	1 lb.
21-431L	Wide Double Bend	6"	1.8 GPM	8-1/2"	1.25 lbs.
21-432L	Wide Double Bend	8-1/2"	1.8 GPM	11"	1.75 lbs.
21-433L	Wide Double Bend	4-1/2"	1.8 GPM	3-3/8"	1 lb.
21-435L	Jointed	24"	1.8 GPM	5-3/4"	2 lbs.
21-227L	Wide Rigid Gooseneck	3-3/4"	0.5 GPM	4-1/2"	0.5 lbs.
21-228L	Wide Rigid Gooseneck	5-3/4"	0.5 GPM	4-5/8"	1 lb.
21-229L	Wide Rigid Gooseneck	8"	0.5 GPM	7"	1 lb.

Add suffix "-X" to model number to specify no aerator installed

### Warning:

Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes

### California Prop 65 Warning:

This product can expose you to chemicals including lead and lead compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.