

Max T-Towers



Standard Features

- Glycol cooled aluminum block standard in tower
- Available in brushed stainless steel (S), polished chrome (C), and polished brass (B)
- Pressurized for Krowne's standard 30 PSI beer system
- Ability to change faucet type per beverage
- Ability to have any custom finish applied
- Constructed and assembled in the USA
- Faucets and handles not included
- Faucet upgrades available
- Drip tray with cut out

Model	Faucets	Overall Length (A)	(1) Arm Faucet to Faucet (B)	End Faucet to End Faucet (C)	End to Center (D)	Faucet Centers	Pipe Diameter
KMT-4	4	21"	3"	16-1/2"	10-1/2"	3"	4"
KMT-6	6	27"	6"	22-1/2"	13-1/2"	3"	4"
KMT-8	8	33"	9"	28-1/2"	16-1/2"	3"	4"
KMT-10	10	39"	12"	34-5/8"	19-1/2"	3"	4"
KMT-12	12	45"	15"	40-5/8"	22-1/2"	3"	4"
KMT-14	14	51"	18"	46-3/8"	25-1/2"	3"	4"
KMT-16	16	57"	20-7/8"	52-3/8"	28-1/2"	3"	4"

Add suffix to model number to specify finish. S = Brushed Stainless Steel, B = Polished Brass, C = Polished Chrome (Example: KMT-10S)

