KROWNE®

Model: _____ **Item #:** _____ **Date:** _____

Project: _____ **Qty:** _____ **Approved By:** _____

Economy Series Casters

Casters





Standard Features


- Fits most manufacturers
- Grease resistant polypropylene wheels
- Zinc plated steel universal plate
- Warranty: 3 years

Specifications


Hole Pattern (A)	Fits 1-3/4" x 2-3/4" or 2-3/4" x 2-3/4"
Hole Pattern (B)	Fits 1-3/4" x 2-3/4"
Hole Pattern (C)	Fits 4-1/8" x 4-1/8" x 5-3/4"

Plated Casters


Model	Plate Size (in.)	Wheel Diameter	Temperature Range	Load Capacity (per caster)	Raises Equipment	Brakes	Weight (Of Set)	Pieces Per Set	Hole Pattern
30-107S	4" x 4"	5"	14°F - 212°F	350 lbs	6"	2 with side lock 2 without side lock	10 lbs	4	A
30-111S	3-1/2" x 3-1/2"	5"	14°F - 212°F	350 lbs	6"	2 with side lock 2 without side lock	10 lbs	4	A
30-113S	2-1/2" x 3-5/8"	5"	14°F - 212°F	350 lbs	6"	2 with side lock 2 without side lock	9 lbs	4	B
30-161S	5-3/8" x 5-3/8" x 7-1/2"	5"	14°F - 212°F	350 lbs	6"	2 with side lock 2 without side lock	14 lbs	4	C
30-117S	3-1/2" x 3-1/2"	3"	14°F - 212°F	210 lbs	8-1/2"-10"	2 with side lock 2 without side lock	16 lbs	4	A




30-107S



30-111S / 30-117S



30-113S



30-161S

Stem Casters

Model	Stem Diameter	Type	Wheel Diameter	Temperature Range	Load Capacity (per caster)	Raises Equipment	Brakes	Thread Size	Weight (Of Set)	Pieces Per Set
30-125S	1-5/8"	Expandable Stem	5"	14°F - 212°F	250 lbs	6"	Side lock on all 4	-	10 lbs	4
30-129S	1-1/2"	Expandable Stem	5"	14°F - 212°F	350 lbs	6"	2 with side lock 2 without side lock	-	10 lbs	4
30-141S	-	Threaded Stem	5"	14°F - 212°F	350 lbs	6"	2 with side lock 2 without side lock	1/2"-13 x 1"	9 lbs	4
30-146S	-	Threaded Stem	5"	14°F - 212°F	350 lbs	6"	2 with side lock 2 without side lock	3/4"-10 x 1"	10 lbs	4
30-151S	7/8"	Friction Grip Ring	5"	14°F - 212°F	350 lbs	6"	2 with side lock, 2 without side lock	-	10 lbs	4