

Model:\_ Project: Item #: \_\_\_\_\_ Date:\_

\_\_\_\_ Approved By:\_\_

# Gas Connector Complete Kit For Canada

**Gas Connectors** 



## Includes:

No.	Name	Description
1	Gas Connector	For stationary and caster-mounted kitchen equipment.
2	Quick Disconnect	Easily disconnects gas hose to move equipment for maintenance and cleaning.
3	Shut-off Valve	Required by code to allow manual shutoff within 6 ft. of appliance.
4	Restraining Cable Kit	Prevents hose from being pulled too far. Includes mounting hardware.
5	(2) 90° Elbows with Nipples	Gives versatility during installation.

Visit krowne.com for complete replacement parts.

### **Product Compliance**

- ANSI Z21.41-2014 CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 CSA 6.16a-2012 Addenda

#### **Standard Features**

Qty:\_\_\_\_\_

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360°
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

#### **Specifications** Pressure 1/2 psi **End Fittings** Carbon Steel, Chrome Plated Tubing Stainless Steel 304 Braiding Stainless Steel 304

Model No.	Interior Size	Length	BTU/hr
C5024K	1/2"	24"	87K
C5036K	1/2"	36"	77K
C5048K	1/2"	48"	68K
C5060K	1/2"	60"	60K
C5072K	1/2"	72"	55K
C7524K	3/4"	24"	232K
C7536K	3/4"	36"	218K
C7548K	3/4"	48"	180K
C7560K	3/4"	60"	158K
C7572K	3/4"	72"	139K
C10024K	1"	24"	414K
C10036K	1"	36"	379K
C10048K	1"	48"	334K
C10060K	1"	60"	294K
C10072K	1"	72"	279K
C12524K	1-1/4"	24"	699K
C12536K	1-1/4"	36"	615K
C12548K	1-1/4"	48"	541K
C12560K	1-1/4"	60"	476K
C12572K	1-1/4"	72"	419K

WARNING: Restraining Kits are required by law for all moveable gas equipment California Proposition 65 Warning



