

Model:	Item #:	Date:
	·	

Project:_____ Qty:____ Approved By:_____

Gas Connector Kit 10

Gas Connectors



Standard Features

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

Specifications

Pressure	■ 1/2 psi	
End Fittings Carbon Steel, Chrome Plated		
Tubing	oing ■ Stainless Steel 304	
Braiding	Stainless Steel 304	

Includes:

No.	Name	Description	
1	Gas Connector	Designed for moveable caster- mounted kitchen equipment.	
2	Quick Disconnect	Easily disconnects gas hose to move equipment for maintenance and cleaning.	
3	Shut-off Valve	Required by code to allow manual shutoff within 6 ft. of appliance.	
4	Restraining Prevents hose from being pulle far. Includes mounting hardwar		
5	(2) 90° Elbows	Gives versatility during installation.	
6	(2) SwivelKing™	Stainless steel construction with dual 360° rotation significantly reduces stress.	

Visit krowne.com for complete replacement parts.

Product Compliance

- ANSI Z21.41-2014 CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 CSA 6.16a-2012 Addenda

Model No.	Interior Size	Length	BTU/hr
M5024K10	1/2"	24"	87K
M5036K10	1/2"	36"	77K
M5048K10	1/2"	48"	68K
M5060K10	1/2"	60"	60K
M5072K10	1/2"	72"	55K
M7524K10	3/4"	24"	232K
M7536K10	3/4"	36"	218K
M7548K10	3/4"	48"	180K
M7560K10	3/4"	60"	158K
M7572K10	3/4"	72"	139K
M10024K10	1"	24"	414K
M10036K10	1"	36"	379K
M10048K10	1"	48"	334K
M10060K10	1"	60"	294K
M10072K10	1"	72"	279K
M12524K10	1-1/4"	24"	699K
M12536K10	1-1/4"	36"	615K
M12548K10	1-1/4"	48"	541K
M12560K10	1-1/4"	60"	476K
M12572K10	1-1/4"	72"	419K

WARNING: Restraining Kits are required by law for all moveable gas equipment California Proposition 65 Warning

