



SCAN TO  
LEARN MORE

FOLLOW US:  




  
[www.krowne.com](http://www.krowne.com)

FLAWLESS. FILTERED. FRESH.

# HydroSift

BY KROWNE

Krowne's HydroSift™ Water Filters are the premier foodservice water filtration solution. Our bacteriostatic filters diminish limescale, reduce chlorine/chloramine, and eliminate bad tastes and odors. The result is clean and safe drinking water ready to serve to your customers.



SHOWN  
KR-HS2-KIT

- ▶ HydroSift is the perfect water filtration solution for any ice machine, steamer, beverage equipment, or coffee brewer
- ▶ Max flow rate varies from 2.5 GPM (KR-HSA, KR-HS1-KIT, and KR-HS2-KIT) to 8.0 GPM (KR-HS3-KIT)
- ▶ Gallon capacity varies from 10,000 (KR-HSA, and KR-HS1-KIT), 15,000 (KR-HS2-KIT), or 20,000 (KR-HS3-KIT)
- ▶ 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- ▶ 35° - 160°F operating temperature

MODEL	DESCRIPTION
KR-HS1-KIT	Single Filter Assembly Kit
KR-HS2-KIT	Twin Filter Assembly Kit
KR-HS3-KIT	Triple Filter Assembly Kit
KR-HSA	Single Assembly with Filter Cartridge
KR-FC	Filter Cartridge
KR-SF	Sediment Filter Cartridge
23-200	3/4" PVC Ball Valve, NPT Male-Female
23-201	3/4" NPT Female Tee Fitting
23-202	3/4" x 1/4" Reducing Bushing
23-203	Pressure Gauge
23-204	3/4" x 3/4" Male to Male Nipple Fitting



SCAN TO  
LEARN MORE

FOLLOW US:  




  
[www.krowne.com](http://www.krowne.com)



### Single Assembly with Filter Cartridge

#### KR-HSA

- 10,000 gallon capacity
- 2.5 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



### Single Water Filter Assembly Kit

#### KR-HS1-KIT

- 10,000 gallon capacity
- 2.5 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



### Twin Water Filter Assembly Kit

#### KR-HS2-KIT

- 15,000 gallon capacity
- 2.5 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



### Triple Water Filter Assembly Kit

#### KR-HS3-KIT

- 20,000 gallon capacity
- 8.0 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



### Filter Cartridge

#### KR-FC

- Bacteriostatic filter
- Diminishes limescale, reduces chlorine chloramine, and eliminates bad taste and odor
- For use in single, twin, and triple filter assemblies



### Sediment Filter Cartridge

#### KR-SF

- Reduces sediment and silk
- For use in twin and triple filter assemblies