

HydroSift™ Water Filters



Krowne's HydroSift™ Water Filters are the premier foodservice water filtration solution. Our bacteriostatic filters diminishes limescale, reduces chlorine/chloramine, and eliminates bad tastes and odor. The result is a clean and safe water ready to serve to your customers.

- NSF/ANSI 42
- NSF/ANSI 53

- Bacteriostatic filters diminishes limescale, reduces chlorine/ chloramine, and eliminates bad tastes and odor
- Granular activated carbon removes chlorine, lime scale, unpleasant taste and bad odor from your water
- Keeps ice and beverage equipment operating efficiently
- Reduces maintenance costs
- 100°F maximum temperature on sediment cartridges
- 3.0 GPM flow on sediment cartridges
- Sediment filter cartridges remove dirt, sand, rust, silt (used only on twin and triple kits)

Model	KR-HS1-KIT	KR-HS2-KIT	KR-HS3-KIT	KR-HSA
Description	Single Filter Assembly Kit	Twin Filter Assembly Kit	Triple Filter Assembly Kit	Single Assembly w/ Filter
Connections	3/4" NPT water in and out	3/4" NPT water in and out	3/4" NPT water in and out	3/4" NPT water in and out
Flow Rate	3.0 GPM	3.0 GPM	3.0 GPM	3.0 GPM
Gallon Capacity	10,000	15,000	20,000	10,000
Pressure	20-100 PSI non-shock (1.38-6.89 bar)	20-100 PSI non-shock (1.38-6.89 bar)	20-100 PSI non-shock (1.38-6.89 bar)	20-100 PSI non-shock (1.38-6.89 bar)
Operating Temp	35°F - 160°F	35°F - 160°F	35°F - 160°F	35°F - 160°F
Overall Size	5-1/2"W x 14"H x 5-1/2"D	10"W x 14"H x 6-1/2"D	17"W x 14"H x 6-1/2"D	5-1/2"W x 14"H x 5-1/2"D

KR-HS3-KIT Triple Filter Assembly Kit

- Triple filter assembly
- Mounting bracket
- (2) Filter cartridge
- (1) Sediment filter cartridge
- (3) Male to male nipple fittings
- Male to female ball valve
- Reducing bushing
- Female tee fitting
- Pressure gauge
- Filter wrench



KR-HS2-KIT Twin Filter Assembly Kit

- Twin filter assembly
- Mounting bracket
- (1) Filter cartridge
- (1) Sediment filter cartridge
- (2) Male to male nipple fittings
- Male to female ball valve
- Reducing bushing
- Female tee fitting
- Pressure gauge
- Filter wrench



KR-HS1-KIT Single Filter Assembly Kit

- Single filter assembly
- Mounting bracket
- (1) Filter cartridge
- Male to male nipple fitting
- Male to female ball valve
- Reducing bushing
- Female tee fitting
- Pressure gauge
- Filter wrench



KR-HSA Single Assembly with Filter

- Single filter assembly
- Mounting bracket
- (1) Filter cartridge



Replacement Filter Cartridges

Model	Description
KR-FC	Filter Cartridge. For use in Single, Twin or Triple Assembly
KR-SF	Sediment Cartridge. For use in Twin or Triple Assembly

Recommended cartridge replacement every 6 months.



Model	Description
23-200	3/4" PVC Ball Valve, NPT Male-Female
23-201	3/4" NPT Female Tee Fitting
23-202	3/4" x 1/4" Reducing Bushing
23-203	Pressure Gauge
23-204	3/4" x 3/4" Male to Male Nipple Fitting
23-205	Wrench for Water Filter
23-206	3/4" NPTM to 1/2" CTS Reducing Adapter

Replacement Components

