

[{View as Webpage}](#)

DID YOU
KNOW WE HAVE...?



HydroSift



Krowne's HydroSift™ Water Filters are the premier foodservice water filtration solution. Our bacteriostatic filters diminishes limescale, reduces chlorine/chloramine, and eliminates bad tastes and odor. The result is a clean and safe water ready to serve to your customers.

Single Assembly with Filter Cartridge

- Bacteriostatic filters diminishes limescale, reduces chlorine/chloramine, and eliminates bad tastes and odor
- Granular activated carbon removes rust, lead, dirt, chlorine, lime scale, unpleasant taste and bad odor from your water
- Keeps ice and beverage equipment operating efficiently
- Reduces maintenance costs
- 100°F maximum temperature on sediment cartridges
- 10 GPM/38 LPM flow on sediment cartridges
- 3/4" NPT water in and out connections
- 2.5 GPM max flow rate
- 10,000 gallon capacity
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



KR-HSA

Hydrosift Single Water Filter Assembly Kit

- Bacteriostatic filters diminishes limescale, reduces chlorine/chloramine, and eliminates bad tastes and odor
- Granular activated carbon removes rust, lead, dirt, chlorine, lime scale, unpleasant taste and bad odor from your water
- Keeps ice and beverage equipment operating efficiently
- Reduces maintenance costs
- 100°F maximum temperature on sediment cartridges

- 10 GPM/38 LPM flow on sediment cartridges
- 3/4" NPT water in and out connections
- 2.5 GPM max flow rate
- 10,000 gallon capacity
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp

KR-HS1-KIT



Hydrosift Twin Water Filter Assembly Kit

- Bacteriostatic filters diminishes limescale, reduces chlorine/chloramine, and eliminates bad tastes and odor
- Granular activated carbon removes rust, lead, dirt, chlorine, lime scale, unpleasant taste and bad odor from your water
- Keeps ice and beverage equipment operating efficiently
- Reduces maintenance costs
- 100°F maximum temperature on sediment cartridges
- 10 GPM/38 LPM flow on sediment cartridges
- 3/4" NPT water in and out connections
- 2.5 GPM max flow rate
- 15,000 gallon capacity
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp

KR-HS2-KIT



Hydrosift Triple Water Filter Assembly Kit

- Bacteriostatic filters diminishes limescale, reduces chlorine/chloramine, and eliminates bad tastes and odor
- Granular activated carbon removes rust, lead, dirt, chlorine, lime scale, unpleasant taste and bad odor from your water
- Keeps ice and beverage equipment operating efficiently
- Reduces maintenance costs
- 100°F maximum temperature on sediment cartridges
- 10 GPM/38 LPM flow on sediment cartridges
- 3/4" NPT water in and out connections
- 8.0 GPM max flow rate
- 20,000 gallon capacity
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp

KR-HS3-KIT



HydroSift Filter Cartridge for Water Filters

- Bacteriostatic filter
- Diminishes limescale, reduces chlorine/chloramine, and eliminates bad taste & odor
- For use in Single, Twin, and Triple Filter Assemblies

KR-FC



Hydrolife Sediment Filter Cartridge for Water Filters

- Reduces sediment and silt
- For use in Twin and Triple Filter Assemblies

KR-SF



Exclusive Promo Code Below!

Click
Here!



Krowne Metal Corporation | 100 Haul Rd | Wayne, NJ 07470 US

[Unsubscribe](#) | [Update Profile](#) | [Constant Contact Data Notice](#)



Try email marketing for free today!