

Specifications

Warranty:
(90) days install
(1) year parts & labor
(5) years compressor

		KPP20-1	KPP33-1	KPP50-1	KPP50-2	KPP75-1	KPP75-2	KPP75-1-230	KPP75-2-230	KPP75-3-230	KPP150-1-230	KPP150-2-230	KPP150-3-230
Electrical	Voltage	120V	120V	120V	120V	120V	120V	230V**	230V**	230V**	230V**	230V**	230V**
	Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
	Phase	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø
	Electrical Connection	Cord & Plug NEMA 5-20P	Cord & Plug NEMA 5-20P	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire
120V Single Pump (Models ending '-1')	RLA	11A	12.5A	15.3A	-	19.6A	-	-	-	-	-	-	-
	MCA	20A	20A	20A	-	25A	-	-	-	-	-	-	-
120V Double Pump (Models ending '-2')	RLA	-	-	-	21.3A	-	24.5A	-	-	-	-	-	-
	MCA	-	-	-	25A	-	30A	-	-	-	-	-	-
230V Single Pump (Models ending '-1-230')	RLA	-	-	-	-	-	-	11A	-	-	13.2A	-	-
	MCA	-	-	-	-	-	-	20A	-	-	20A	-	-
230V Double Pump (Models ending '-2-230')	RLA	-	-	-	-	-	-	-	14A	-	-	16A	-
	MCA	-	-	-	-	-	-	-	20A	-	-	25A	-
230V Triple Pump (Models ending '-3-230')	RLA	-	-	-	-	-	-	-	-	17A			18A
	MCA	-	-	-	-	-	-	-	-	25A			30A
Length (A)		27"	27"	27"	27"	27"	27"	27"	27"	27"	27"	27"	27"
Width (B)		17"	17"	17"	17"	20"	20"	20"	20"	20"	20"	20"	20"
Height (C)		24-1/2"	24-1/2"	24-1/2"	24-1/2"	26"	26"	26"	26"	26"	29-3/4"	29-3/4"	29-3/4"
Weight (lbs.)		119	124	129	143	159	173	159	173	187	185	200	215
Compressor		1/5 HP	1/3 HP	1/2 HP	1/2 HP	3/4 HP	3/4 HP	3/4 HP	3/4 HP	3/4 HP	1.5 HP	1.5 HP	1.5 HP
Evaporator Rating @ 15° F (BTUH)		1680	2600	4100	4100	6950	6950	6950	6950	6950	10800	10800	10800
Heat Rejection (average)		2184	3380	5330	5330	9035	9035	9035	9035	9035	14040	14040	14040
Refrigerant		R134A	R134A	R134A	R134A	R134A	R134A	R134A	R134A	R134A	R448A	R448A	R448A
Cabinet Material		Stainless Steel											
Circulating Pump		80 GPH / 100 PSI											
Reservoir Capacity (gallons)		1.8											
Refrigerant Charge		12.5 oz.	14 oz.	15.5 oz.	15.5 oz.	20 oz.	20 oz.	20 oz.	20 oz.	20 oz.	36 oz.	36 oz.	36 oz.
Glycol Concentration		33%	33%	33%	33%	33%	33%	33%	33%	33%	33%	33%	33%

RLA = Rated Load Amps
MCA = Minimum Circuit Ampacity

** 230V models require four wires - 2 hot, 1 neutral, and 1 ground

