

## Spouts

## ROYAL SERIES



21-420L



21-428L



21-430L

### Standard Features

- Durable full range spout with double o-ring construction
- Chrome plated finish
- Built for high volume
- Fits all Krowne faucets and interchangeable with most brands
- 3 year warranty

### Product Compliance

#### 21-42 & 21-43 Models

- NSF-61 & NSF/ANSI 372
- NSF/ANSI/CAN 61: Q<1
- ASME A112.18.1-2012/CSA B125.1-12
- CEC Listed
- Massachusetts Listed



#### 21-22 Models

- NSF-61 & NSF/ANSI 372
- NSF/ANSI/CAN 61: Q<1
- ASME A112.18.1-2012/CSA B125.1-12 & NSF/ANSI 372

| Model   | Spout Style          | Spout Length | Flow Rate | Height | Weight    |
|---------|----------------------|--------------|-----------|--------|-----------|
| 21-420L | Swing                | 6"           | 1.8 GPM   | 1"     | 0.5 lbs.  |
| 21-421L | Swing                | 8"           | 1.8 GPM   | 1"     | 0.5 lbs.  |
| 21-422L | Swing                | 10"          | 1.8 GPM   | 2-1/4" | 0.75 lbs. |
| 21-423L | Swing                | 12"          | 1.8 GPM   | 2-5/8" | 0.75 lbs. |
| 21-424L | Swing                | 14"          | 1.8 GPM   | 3-1/2" | 0.75 lbs. |
| 21-425L | Swing                | 16"          | 1.8 GPM   | 4"     | 0.75 lbs. |
| 21-426L | Jointed              | 18"          | 1.8 GPM   | 4-1/8" | 1.25 lbs. |
| 21-427L | Wide Gooseneck       | 3-1/2"       | 0.5 GPM   | 7-1/4" | 0.5 lbs.  |
| 21-428L | Wide Gooseneck       | 6"           | 1.8 GPM   | 8-1/2" | 0.75 lbs. |
| 21-429L | Wide Gooseneck       | 8-1/2"       | 1.8 GPM   | 10"    | 0.5 lbs.  |
| 21-430L | Wide Double Bend     | 4-1/2"       | 0.5 GPM   | 6"     | 1 lb.     |
| 21-431L | Wide Double Bend     | 6"           | 1.8 GPM   | 8-1/2" | 1.25 lbs. |
| 21-432L | Wide Double Bend     | 8-1/2"       | 1.8 GPM   | 11"    | 1.75 lbs. |
| 21-433L | Wide Double Bend     | 4-1/2"       | 1.0 GPM   | 3-3/8" | 1 lb.     |
| 21-435L | Jointed              | 24"          | 1.8 GPM   | 5-3/4" | 2 lbs.    |
| 21-227L | Wide Rigid Gooseneck | 3-3/4"       | 0.5 GPM   | 4-1/2" | 0.5 lbs.  |
| 21-228L | Wide Rigid Gooseneck | 5-3/4"       | 0.5 GPM   | 4-5/8" | 1 lb.     |
| 21-229L | Wide Rigid Gooseneck | 8"           | 0.5 GPM   | 7"     | 1 lb.     |

Add suffix "-X" to model number to specify no aerator installed

#### Warning:

Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes

#### California Prop 65 Warning:

This product can expose you to chemicals including lead and lead compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.cdph.ca](http://www.cdph.ca)