

# Stationary Gas Connector

## ROYAL SERIES



### Standard Features

- For use on Stationary Commercial Gas Appliances only
- Durable steel fittings - heavy duty corrosion-resistant construction extends longevity
- Antimicrobial yellow coating - PVC protective coating provides durability and ease to clean
- Stainless steel tubing
- Variable lengths and interior diameters available
- 0.5 PSI maximum operation pressure
- Suitable for indoor and outdoor use
- Safe & easy installation

| Model   | I.D. | Length | BTU/hr. Flow * | Includes                                 | Packed In |
|---------|------|--------|----------------|--|-----------|
| S7536   | 3/4" | 36"L   | 256,000        | Gas Connector                            | Poly Bag  |
| S7536B  | 3/4" | 36"L   | 256,000        | Gas Connector                            | Color Box |
| S7536K  | 3/4" | 36"L   | 256,000        | Gas Connector, (2) 90° Elbows, Gas Valve | Color Box |
| S7536K1 | 3/4" | 36"L   | 256,000        | Gas Connector, (2) 90° Elbows            | Color Box |
| S7548   | 3/4" | 48"L   | 225,000        | Gas Connector                            | Poly Bag  |
| S7548B  | 3/4" | 48"L   | 225,000        | Gas Connector                            | Color Box |
| S7548K  | 3/4" | 48"L   | 225,000        | Gas Connector, (2) 90° Elbows, Gas Valve | Color Box |
| S7548K1 | 3/4" | 48"L   | 225,000        | Gas Connector, (2) 90° Elbows            | Color Box |
| S5036   | 3/4" | 36"L   | 256,000        | Gas Connector, 1/2" Reducer              | Poly Bag  |
| S5036B  | 3/4" | 36"L   | 256,000        | Gas Connector, 1/2" Reducer              | Color Box |
| S5036K  | 3/4" | 36"L   | 256,000        | Gas Connector, 1/2" Reducer              | Color Box |
| S5048   | 3/4" | 48"L   | 256,000        | Gas Connector, 1/2" Reducer              | Poly Bag  |
| S5048B  | 3/4" | 48"L   | 256,000        | Gas Connector, 1/2" Reducer              | Color Box |
| S5048K  | 3/4" | 48"L   | 256,000        | Gas Connector, 1/2" Reducer              | Color Box |

\* This connector meets or exceeds time minimum allowable capacity as determined under test conditions specified in ANSI Z21.24 CSA 6.10. Straight Length Capacity - BTU/hr), 0.64 SP. GR. @ 0.5 inch Water Column (125 Pa) Pressure Drop. 1,000 BTU Per cubic ft. (37.2 MJ Per cubic meter)

#### Durable Steel Swivel

- Heavy duty swivel fittings are corrosion-resistant and extends

#### Antimicrobial Yellow

- PVC protective coating applied for added strength and durability

#### Stainless Steel Construction

- 304 stainless steel tubing provides flexibility and versatility during



#### Warning:

Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes

### Product Compliance

- NSF/ANSI Std. 169
- ANSI Z21.24-22 CSA 6.10-22



Learn more at [krowne.com/warranty](http://krowne.com/warranty)

#### Warning:

Stationary gas connectors are designed for occasional movement after installation of stationary or fixed appliances only. Repeated bending, flexing, torsion or excessive vibration must be avoided. Normal operation of a clothes dryer, rooftop HVAC unit or similar gas appliance does not constitute extreme vibration or movement.

Stationary Gas Connectors are NOT to be installed on Moveable Commercial Gas Appliances. Product mishandling and/or misuse will void warranty.

Connections should be made by qualified personnel who will observe all applicable safety codes.

#### California Prop 65 Warning:

This product can expose you to chemicals including lead and lead compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).